

Page : 1 of 9
Revision No: 2

Date : OCT. 27, 2025

PRODUCT NAME: CEYPETCO PENETRATING OIL

SECTION 1 IDENTIFATION OF SUBSTANCES / PREPARATION AND COMPANY

PRODUCT DETAILS

Product Name: Ceypetco Penetrating Oil

Product Description: Penetrating oil.

COMPANY IDENTIFICATION

Supplier's Name : Ceylon Petroleum Corporation
Supplier's Address : No. 609, Dr Danister De Silva

Mawatha, Baseline Road, Dematagoda Colombo-09

Emergency Tel. No. : +94-11 5455455 Fax No. : +94-11545540

SECTION 2 HAZARDS IDENTIFICATION

Emergency Overview

Contents under pressure. Do not puncture, incinerate or expose to temperature above 120F(49 °C). Eye, skin and respiratory irritant. Harmful if inhaled.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: Exposure may be by inhalation and/or skin or eye contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation and personal protective equipment.

Eye Contact: May cause eye irritation. Redness and itching or burning sensation may indicate excessive exposure. Skin

Contact: May cause skin irritation. Redness and itching or burning sensation may indicate

excessive exposure.

Inhalation: May cause irritation of the respiratory system. May cause nervous

system depression. Headache, nausea, dizziness and loss of coordination are indications of excessive exposure to vapors or spray mists. Extreme overexposure may result in unconsciousness

and possibly death.

General: Reports have associated repeated and prolonged overexposure to

solvents with permanent brain and nervous system damage. Headache, dizziness, nausea and loss of coordination are indication of excessive

exposure to vapors or spray mists.

Ceylon Petroleum Corporation

No. 609, Dr. Danister De Silva Mawatha, Baseline Road, Dematagoda, Colombo 09, Sri Lanka Tel:+94 11 5455 455 Fax: + 94-11 5455 400



Page : 2 of 9
Revision No: 2

Date : OCT. 27, 2025

PRODUCT NAME: CEYPETCO PENETRATING OIL

SECTION 3 COMPOSITION/ INFORMATION ON INGREDIENTS						
Hazardous Ingredients	CAS Number	Weigh t	ACGIH	OSHA		
Perchloroethylene	127-18-4	<80%	25 ppm	25 ppm		
Heavy Naphthenic Petroleum C	oil 64742 -52-5	<10%	5 mg/m3 as mist	5 mg/m3 as mist		
Mineral Oil	64741 -88-4	<15%	5 mg/m3 as mist	5 mg/m3 as mist		
Propylene Glycol T-Butyl Ether	57018 -52-7	<12%	NE	NE		
Carbon Dioxide	124-38-9	<15%	5000 ppm	5000 ppm		

SECTION 4 FIRST AID MEASURES

Eye Contact:

Promptly flush with a large amount of water for at least 15 minutes. If irritation persists, consult at physician.

Skin Contact: Promptly wash with soap and water and rinse thoroughly.

Remove contaminated clothing and launder before reuse.

If irritation persists, consult at physician.

Inhalation: Remove to fresh air. Restore breathing if necessary.

If irritation persists, consult a physician.

Ingestion: Do not induce vomiting. Never give anything by mouth to an

unconscious person. Seek immediate medical attention



Page: 3 of 9
Revision No: 2

Date : OCT. 27, 2025

PRODUCT NAME: CEYPETCO PENETRATING OIL

SECTION 5 FIRE FIGHTING MEASURES

Flashpoint (Method): No flame extension. Non-Flammable.

Lower Explosive Limit(LEL): 1.8 Upper Explosive Limit(UEL): 6.8 Autoignition

Temperature: NA

Fire and Explosion Hazards: Closed containers may explode, due to the build-up of

pressure, when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

Extinguishing Media: Carbon dioxide, dry chemical, foam.

Fire Fighting Instructions: Full protective equipment including self-contained

breathing apparatus should be used. Water spray maybe ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Remove all sources of ignition. Ventilate and remove with inert absorbent. Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Do not incinerate. Depressurize container. Dispose foin accordance with all Federal, State and Local Regulations regarding pollution and waste disposal.



Page : 4 of 9
Revision No: 2

Date : OCT. 27, 2025

PRODUCT NAME: CEYPETCO PENETRATING OIL

SECTION 7 HANDLING AND STORAGE

Keep away from heat, flames, sparks or other sources of ignition. Consult NFPA Code. Use approved bonding and grounding procdeures. Contents under pressure. Do not puncture, incinerate or expose to temperature above 120F(49 °C). Heat from sunlight, radiators, stoves, hot water and other heat sources could cause container to burst. Do not take internally. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Keep out of reach of children. Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.



Page : 5 of 9
Revision No: 2

Date : OCT. 27, 2025

PRODUCT NAME: CEYPETCO PENETRATING OIL

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Local exhaust preferable. General exhaust acceptable if the exposure to materials is maintained below applicable exposure limits. Personal Protective Equipment:

Respiratory: If personal exposure cannot be controlled below applicable limits by

ventilation, wear a properly fitted NIOSH-approved organic

vapor/particulate respirator.

Eye: Wear approved safety glasses with unperforated sideshields.

Skin: Wear chemically impervious gloves.

Other: An emergency eyewash station should be available in case of accidental eye

contact.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Bright & Clear

Physical State :- Liquid

Density @ 30 C- 0.782 Kg/L

Boiling Point- $< 1-307 \text{ F: } < -18 - 152 \text{ }^{\circ}\text{C}$

Melting Point: N/A

Evaporation Rate: Faster Either

Vapour Pressure @ 0 F- N/A

PH : N/A

SPECIFIC GRAVITY -1.34

Volatile Volume: 81%

Vapor Density: Heavier Than Air

Solubility in Water: N/A



Page : 6 of 9 Revision No: 2

Date : OCT. 27, 2025

PRODUCT NAME: CEYPETCO PENETRATING OIL

SECTION 10 STABILITY AND REACTIVITY

Stability: Stable.

Hazardous Polymerization: Will not occur.

Conditions to Avoid: Heat, sparks, flames or other

sources of ignition. Incompatibility: None expected.

Hazardous Decomposition Products: By Fire: Carbon Dioxide, Carbon Monoxide,

Hydrogen Chloride.

SECTION 11 TOXICOLOGICAL INFORMATION

Perchloroethylene is listed by NTP and IARC as an animal carcinogen and by OSHA as a potential human carcinogen.

<u>Hazardous Ingredients</u>	CAS Number	<u>LD50</u>	<u>LC50</u>
Perchloroethylene	127-18-4	2629 mg/kg (oral rat)	5040 ppm /8 hr (rat)
Heavy Naphthenic Petroleum Oil	64742 -52-5	NE	NE
Mineral Oil	64741 -88-4	NE	NE
Propylene Glycol T-Butyl Ether	57018 -52-7	NE	NE
Carbon Dioxide	124-38-9	NE	Trout 240 mg/l/1 hour



Page: 7 of 9
Revision No: 2

Date : OCT. 27, 2025

PRODUCT NAME: CEYPETCO PENETRATING OIL

SECTION 12 ECOLOGICAL INFORMATION

Marine Pollutant.

SECTION 13 DISPOSAL CONSIDERATIONS

Do not incinerate. Depressurize container. Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act C(RA) 40 CFR 261. RCRA Code for Perchloroethylene is U210. Dispose of in accordance with Federal, State and Local Regulations regarding pollution and waste disposal.

SECTION 14 TRANSPORT INFORMATION

DOT Shipping Data: Consumer Commodity, ORM-D

Canadian TDG: Shipped in accordance with 49 CFR as part of a transborder

shipment authorized under Section 5.2 (1) of the Canadian

Transportation of Dangerous Goods.

For International and Air Shipments: Aerosols, NonFlammable, Containing Substances in Division 6.1, Packing Group III, 2, UN1950. Marine Pollutant.

SECTION 15 REGULATORY INFORMATION

TSCA: All ingredients in this product are listed or exempt from listing on the TSCA Chemical Inventory.

CEPA: All ingredients in this product are listed or

exempt from listing on the Canadian DSL/NDSL.

Proposition 65: This product contains a chemical known to the state of California to cause cancer, birth defects or other reproductive harm. (Perchloroethylene).

Ceylon Petroleum Corporation

No. 609, Dr. Danister De Silva Mawatha, Baseline Road, Dematagoda, Colombo 09, Sri Lanka Tel:+94 11 5455 455 Fax: + 94-11 5455 400



Page: 8 of 9 Revision No: 2

Date : OCT. 27, 2025

PRODUCT NAME: CEYPETCO PENETRATING OIL

SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372.65C):

CHEMICAL CAS# Weight

Perchloroethylene 127-18-4 75%

HMIS Classification: Health = 2

Flammability = 0 Reactivity = 0

Personal Protection = B

WHMIS Classification: Class D, Division 2B



Page: 9 of 9 Revision No: 2

Date : OCT. 27, 2025

PRODUCT NAME: CEYPETCO PENETRATING OIL

SECTION 16 OTHER INFORMATION

NA = Not Available or Not Applicable. NE = Not Established

•

Read and follow all label directions and precautions before using the product. These products arenitended for industrial and institutional use only. NOT FOR HOUSEHOLD USE OR RESALE KEEP OUT OF THE REACH OF CHILDREN. While we believe that the data contained herein is factual and the opinions expressed are those of qualified experts, the data are not to be taken as a warranty or representation for which the company assumes legal responsibility. They are offered solely for your consideration, investigation, and verification. Any use of these data and information must be determined by the user to be act accordance with applicable Federal, State, and Local Laws and regulations.

HEALTH AND SAFETY INFORMATION: (603) 3392-3585

Completed On: April 2014 Replaces: October 2012

The information contained in this data sheet is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.