

## Ceypetco 4T Scooter

### Description

**Ceypetco 4T Scooter** is a high-performance synthetic blend (semi synthetic) SAE 10W-40 multigrade engine oil that is specially formulated for lubrication of modern and high performance four stroke motorcycles. It is blended using highly refined materials and selected superior performance additives to impart exceptionally good engine protection under all operating conditions.

### Features and Benefits

- Exceptional level of engine cleanliness and wear protection even on extended drain intervals.
- Exceptional thermal stability for outstanding performance at high engine operating temperatures.
- Excellent gear micro-pitting for exceptional performance response, acceleration and smooth riding.

### Applications

- Most models of high-performance air and water cooled four stroke motorcycle engines such as scooters, mopeds, ATVs and motorcycles fitted with automatic transmission system.
- Two-stroke motorcycle gearboxes.

### Typical Characteristics

PROPERTIES	METHOD	SAE 10W-30
Density at 15°C, g/cm <sup>3</sup>	ASTM D4052	0.8713
Flash Point, °C (C.O.C)	ASTM D92	>210
Viscosity at 40°C, cSt	ASTM D7052	73.6
Viscosity at 100°C, cSt	ASTM D7052	11
Viscosity Index	ASTM D2270	140
Total Base Number, mgKOH/g	ASTM D2896	6

### Performance

- API SL
- JASO MB

## Health, Safety and Environment

Based on available information, this product is not expected to produce adverse effects on health when used for applications referred to above and the recommendations provided in the Safety Data Sheet (SDS) are followed. SDS's are available upon request through your sales contact office. This product should not be used for purpose other than the applications referred to above. If disposing of used product, take care to protect the environment, follow the local rules and regulations of your local Authority.

### **Note:**

All information supplied by or on behalf of Hyrax Oil in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by rigorous laboratory work and research and believed to be reliable.

Typical test data are average values only. Minor variations to typical properties not affecting the performance of the product are to be expected in normal manufacturing circumstances.