

Ceypetco ATF Dexron III D

Ceypetco ATF Dexron III D is a modern, high performance fully synthetic transmission oils primarily intended for use in automatic transmissions systems and in many other applications where Dexron-III D fluid is specified.

It is formulated from highly refined high viscosity index mineral oils and advanced additive systems to provide excellent anti-wear, corrosion resistance, friction retention, and thermal and oxidation stability at high temperatures as well as excellent low temperature characteristics.

Features and Benefits

- Smooth, jerk-free shift performance
- A high level of protection under a wide range of service conditions
- Enhanced protection against wear to prolong transmission life
- Improved cleanliness of transmission system

Applications

Recommended for use in all automatic transmissions, power steering and other hydraulic systems for which a Dexron III D fluid or Allison C-4 type fluid is specified.

Typical Characteristics

Properties	Method	Dexron III D
Color	Visual	Red
Density at 15°C Kg/L	ASTMD4052	0.8740
Flash Point, °C	ASTM D92	>180
Pour Point, °C	ASTM D97	-30
Viscosity at 40°C, cSt	ASTM D7052	40
Viscosity at 100°C, cSt	ASTM D7052	7.5
Viscosity Index	ASTM D2270	187

Performance

- GM Dexron III D

Health, Safety and Environment

Based on available information, this product is not expected to produce adverse effects on health when used for applications referred to above and the recommendations provided in the Safety Data Sheet (SDS) are followed. SDS's are available upon request through your sales contact office. This product should not be used for purpose other than the applications referred to above. If disposing of used product, take care to protect the environment, follow the local rules and regulations of your local Authority.

Note:

All information supplied by or on behalf of Hyrax Oil in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by rigorous laboratory work and research and believed to be reliable.

Typical test data are average values only. Minor variations to typical properties not affecting the performance of the product are to be expected in normal manufacturing circumstances.