

Ceypetco Enduro SAE 15W-40

Ceypetco Enduro SAE 15W-40 is a premium quality multi-grade diesel engine oil specially formulated using highly refined base oils and advanced additive system engineered for modern, high output, low emission engines including those fitted with Exhaust Gas Recirculation (EGR) as well as older turbo-charged engines running on low sulfur diesel or conventional high sulfur diesel fuel and operating under the most severe working conditions.

Features and Benefits

- Excellent protection against corrosive wears and soot-induced wears in severe diesel service.
- Permits longer oil change interval
- Good detergent and dispersant properties

Applications

Ceypetco Enduro SAE 15W-40 is ideal for all high-performance heavy-duty diesel engines, including those fitted with Exhaust Gas Recirculation (EGR) system both on highway and off highway, such as off-road trucks, construction equipment, agricultural equipment and power generators. Also highly recommended for pickup trucks, four-wheel drives (4WD) and sport utility vehicles (SUV) applications.

Typical Characteristics

PROPERTIES	METHOD	SAE Grade
		15W-40
Appearance	Visual	B & C
Density at 15°C, kg/l	ASTM D 4052	0.8720
Flash Point, °C	ASTM D92	>210
Pour Point, °C	ASTM D97	-30
Kinematic viscosity at 40°C, cSt	ASTM D7042	96.7
Kinematic viscosity at 100°C, cSt	ASTM D7042	14.6
Viscosity Index	ASTM D2270	157
Total Base Number, mgKOH/g	ASTM D2896	10.5

Performance

- API CI-4/SL
- Cummin CES 20078

Health, Safety and Environment

Based on available information, this product is not expected to produce adverse effects on health when used for applications referred to above and the recommendations provided in the Safety Data Sheet (SDS) are followed. SDS's are available upon request through your sales contact office. This product should not be used for purpose other than the applications referred to above. If disposing of used product, take care to protect the environment, follow the local rules and regulations of your local Authority.

Note:

All information supplied by or on behalf of Hyrax Oil in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by rigorous laboratory work and research and believed to be reliable.

Typical test data are average values only. Minor variations to typical properties not affecting the performance of the product are to be expected in normal manufacturing circumstances.