

## Ceypetco Penetrating Oil

### Description

**Ceypetco Penetrating Oil** is a clear brownish lubricating fluid that flows between rusty and corroded parts to break the bond of oxidized metal. It penetrates and loosens rust, scale, corrosion and dirt to free corroded parts and fasteners...

It is an effective and efficient general-purpose lubricant for use in household, vehicle and industrial equipment parts. It contains no silicones.

### Features and Benefits

- Does not contain CFC
- Will no effect on painted surfaces
- Low surface tension
- Work as a lubricant

### Applications

Typical applications include releasing rusty or frozen lugs, bolts, screws, fasteners and metal components, general overhaul and repair work and lubricating close fitting parts. This product is used as a lubricant for moving parts.

### Typical Characteristics

Properties	Method	Penetrating Oil
Color and Appearance	Visual	Brown amber low viscosity liquid
Density at 15°C, Kg/L	ASTM D4052	0.92
Flash Point, °C	ASTM D92	146
Pour Point, °C	ASTM D97	-36
Viscosity at 100 °C, cSt	ASTM D445	5.1
Solubility in water	Visual	Insoluble

## Health, Safety and Environment

Based on available information, this product is not expected to produce adverse effects on health when used for applications referred to above and the recommendations provided in the Safety Data Sheet (SDS) are followed. SDS's are available upon request through your sales contact office. This product should not be used for purpose other than the applications referred to above. If disposing of used product, take care to protect the environment, follow the local rules and regulations of your local Authority.

### **Note:**

All information supplied by or on behalf of Hyrax Oil in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by rigorous laboratory work and research and believed to be reliable.

Typical test data are average values only. Minor variations to typical properties not affecting the performance of the product are to be expected in normal manufacturing circumstances.