

Ceypetco Rodeo Xtra

Description

Ceypetco Rodeo Xtra is a premium mineral engine oil series developed with high quality base oils and additive package system that provide a high level of protection against wear, rust and corrosion, piston scuffing and combustion chamber deposits, high temperature oxidation and valve train wear.

Ceypetco Rodeo Xtra gives your engine superior protection and performance in today's modern passenger car engines.

Features and Benefits

- Excellent sealing properties
- Superior wear protection for engines parts
- Exceptional cleansing properties

Applications

Ceypetco Rodeo Xtra is recommended for most passenger cars, sport utility vehicles and light trucks and most turbocharged, supercharged engines operating on gasoline or diesel.

Typical Characteristics

Properties	Method	SAE Grade	
		SAE 10W-30	SAE 15W-40
Appearance	Visual	Clear & Bright	Clear & Bright
Density at 15 °C,	ASTM D4052	0.8591	0.8772
Flash Point, °C (C.O.C)	ASTM D92	>210	>210
Viscosity at 40°C , cSt	ASTM D7052	78.5	120
Viscosity at 100°C, cSt	ASTM D7052	11.3	15.5
Viscosity Index	ASTM D2270	135	135
Total Base Number,	ASTM D2896	10	10

Performance

- API SN/CF
- ILSAC GF-5 (SAE 10W-30)

Health, Safety and Environment

Based on available information, this product is not expected to produce adverse effects on health when used for applications referred to above and the recommendations provided in the Safety Data Sheet (SDS) are followed. SDS's are available upon request through your sales contact office. This product should not be used for purpose other than the applications referred to above. If disposing of used product, take care to protect the environment, follow the local rules and regulations of your local Authority.

Note:

All information supplied by or on behalf of Hyrax Oil in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by rigorous laboratory work and research and believed to be reliable.

Typical test data are average values only. Minor variations to typical properties not affecting the performance of the product are to be expected in normal manufacturing circumstances.