Product Information



Ceypetco Universal Tractor Fluid

Ceypetco Universal Tractor Fluid is a premium quality multi-purpose Super Tractor Oil Universal (STOU) lubricant exclusively designed to meet various lubrication requirements of engines, transmission systems, hydraulic systems, final drives and wet brakes and clutches of most modern farming equipment. It is formulated to meet John Deere tractor requirement specifications and other international standards.

Features and Benefits

Ceypetco Universal Tractor Fluid is designed to provide the following benefits:

- High thermal and oxidation stability
- Excellent antiwear for longer bearing and hydraulic pump life
- Good seal material compatibility
- Good filterability
- Rust and corrosion protection.
- Gear protection for hypoid axles which have completed break-in.

Applications

Recommended for transmissions, differentials, final drives, power take off, oil immersed brakes, power steering and hydraulic systems employing common fluid reservoirs hence eliminate the need for stocking separate engine and transmission lubricants.

Typical Characteristics

PROPERTIES	METHOD	SAE Grade	
		10W-30	15W-40
Appearance	Visual	B & C	B & C
Density at 15°C, kg/l	ASTM D4052	0.870	0.8760
Flash Point, °C	ASTM D92	>210	>210
Pour Point, °C	ASTM D97	-33	-30
Kinematic viscosity at 40°C, cSt	ASTM D7052	65.1	112.8
Kinematic viscosity at 100°C, cSt	ASTM D7052	9.4	14.4
Viscosity Index	ASTM D2270	125	130
Total Base Number, mgKOH/g	ASTM D2896	9	9

Rev: 28/10/2025





Performance

- API CI-4/CF-4/CF/SF
- ACEA E2/E7
- MAN 271
- API GL-4
- Allison C-4
- John Deere JDM J27
- Massey Fergusson CMS M 1145
- Cat TO-2
- MIL-L-210D

Health, Safety and Environment

Based on available information, this product is not expected to produce adverse effects on health when used for applications referred to above and the recommendations provided in the Safety Data Sheet (SDS) are followed. SDS's are available upon request through your sales contact office. This product should not be used for purpose other than the applications referred to above. If disposing of used product, take care to protect the environment, follow the local rules and regulations of your local Authority.

Note:

All information supplied by or on behalf of Hyrax Oil in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by rigorous laboratory work and research and believed to be reliable.

Typical test data are average values only. Minor variations to typical properties not affecting the performance of the product are to be expected in normal manufacturing circumstances.

Rev: 28/10/2025